


DPA050B7WDB

8,500 BTU (5,000 SACC) 3-in-1 Portable Air Conditioner











FEATURES

- Convenient 3-in-1 design: air conditioner, fan, and dehumidifier
- 8,500 BTU (5,000 SACC) portable air conditioner cools spaces up to 150 square feet
- R32 refrigerant: environmentally friendly, R32's GWP (Global Warming Potential) is 3x lower than R410a
- Powerful 2-speed fan
- Dehumidifier mode with direct drain for continuous operation
- Electronic controls with LED display and remote control
- Auto-restart: unit automatically restarts after a power failure
- 24-hour timer
- Single hose design efficiently exhausts warm and humid air outside
- Reusable, washable air filter
- Easy to move castors and integrated handles for easy room-to-room transport
- 24-month warranty on parts and carry-in service

SPECIFICATIONS

rial Meta Electronic Electronic Electronic 165 r 24hrs) 65.96 5000 150 sq.ft 0 rating 8000 BTU R32 2 efrigerant 210 Single Hose rt - Castors Included er Mode - Direct Drain ntrol - Removable Filter ee Standard g (High) 56 dBs g (Low) 52.5 dBs	Colour	White
Electronic 165 r 24hrs) 65.96 5000 150 sq.ft 0 rating 8000 BTU R32 2 efrigerant 210 Single Hose rt - Castors Included er Mode - Direct Drain ntrol - Removable Filter 10 115 V 115 V 9.8 A 824 W	Installation Type	Portable
r 24hrs) 65.96 5000 150 sq.ft 0 rating 8000 BTU R32 2 efrigerant 210 Single Hose rt - Castors Included er Mode - Direct Drain ntrol - Removable Filter ee Standard g (High) 56 dBs g (Low) 52.5 dBs	Primany Material	Metal
r 24hrs) 65.96 5000 150 sq.ft 0 rating 8000 BTU R32 2 efrigerant 210 Single Hose rt - Castors Included er Mode - Direct Drain ntrol - Removable Filter re Standard 19 (High) 56 dBs 19 (Low) 52.5 dBs 115 V 9.8 A 824 W	Control Type	Electronic
150 sq.ft 150 sq.ft 150 sq.ft 150 sq.ft R32 2 2 2 2 2 2 2 2 2 2 2 2 2	Capacity	
5000 150 sq.ft 0 rating 8000 BTU R32 2 efrigerant 210 Single Hose rt - Castors Included er Mode - Direct Drain ntrol - Removable Filter re Standard Ig (High) 56 dBs Ig (Low) 52.5 dBs 115 V 9.8 A 824 W	Airflow	165
150 sq.ft 8000 BTU R32 2 efrigerant 210 Single Hose rt - Castors Included er Mode - Direct Drain ntrol - Removable Filter re Standard g (High) 56 dBs g (Low) 52.5 dBs 115 V 9.8 A 824 W	Capacity (per 24hrs)	65.96
o rating 8000 BTU R32 2 efrigerant 210 Single Hose rt - Castors Included er Mode - Direct Drain ntrol - Removable Filter re Standard g (High) 56 dBs g (Low) 52.5 dBs 115 V 9.8 A 824 W	SACC Rating	5000
o rating 8000 BTU R32 2 efrigerant 210 Single Hose rt - Castors Included er Mode - Direct Drain ntrol - Removable Filter re Standard g (High) 56 dBs g (Low) 52.5 dBs 115 V 9.8 A 824 W	Cooling	
R32 afrigerant 210 Single Hose rt - Castors Included er Mode - Direct Drain ntrol - Removable Filter re Standard Ig (High) 56 dBs Ig (Low) 52.5 dBs 115 V 9.8 A 824 W	Cooling Area	150 sq.ft
2 efrigerant 210 Single Hose rt - Castors Included er Mode - Direct Drain ntrol - Removable Filter re Standard Ig (High) 56 dBs Ig (Low) 52.5 dBs 115 V 9.8 A 824 W	Ashrae (BTU) rating	8000 BTU
efrigerant 210 Single Hose rt Castors Included er Mode · Direct Drain ntrol · Removable Filter re Standard g (High) 56 dBs g (Low) 52.5 dBs 115 V 9.8 A 824 W	Refrigerant	R32
Single Hose rt Castors Included er Mode Throl Castors Included er Mode Castors Include Er Mode Er Mode Castors Include Er Mode Er	Fan Speed	2
er Mode	Amount of Refrigerant	210
er Mode	Hose Туре	Single Hose
er Mode	Features	
ntrol Removable Filter Re Standard g (High) 56 dBs g (Low) 52.5 dBs 115 V 9.8 A 824 W	 Auto Restart 	 Castors Included
e Standard g (High) 56 dBs g (Low) 52.5 dBs 115 V 9.8 A 824 W	 Dehumidifier Mode 	 Direct Drain
Standard g (High) 56 dBs g (Low) 52.5 dBs 115 V 9.8 A 824 W 824 W	 Remote Control 	 Removable Filter
Standard g (High) 56 dBs g (Low) 52.5 dBs 115 V 9.8 A 824 W 824 W	 Timer 	
g (High) 56 dBs g (Low) 52.5 dBs 115 V 9.8 A 824 W	Performance	
g (Low) 52.5 dBs 115 V 9.8 A 824 W	Filter Type	Standard
115 V 9.8 A 824 W	Decibel Rating (High)	56 dBs
9.8 A 824 W	Decibel Rating (Low)	52.5 dBs
9.8 A 824 W	Power	
824 W	Voltage	115 V
	Amperage	9.8 A
	Wattage	824 W
6.1	CEER Rating	6.1
_ength 59.1 "		FO 1 //
	Power Cord Length Weight & Dimensions	59.1

Product WxDxH	12.52" x 12.95" x 24.96" 31.80cm x 32.89cm x 63.40cm
Shipping WxDxH	14.37" x 15.08" x 32.68" 36.50cm x 38.30cm x 83.01cm
Product Weight/Package Weight	53.4 lb (24.22 kg) / 59.1 lb (26.81 kg)

